

## Point to Point Measurement Instructions

- Establish two points, **A** and **B**, at least **20'** or at least **2/3** the length of the pool apart by marking the pool deck or driving two stakes (be sure that these 2 points stay fixed and do not move). **The A point should always be in the shallow end. Place the points far enough away from the pool that an imaginary line extending through A and B in both directions does not cross the perimeter.** There should be a margin of at least **3'** between the imaginary line and the pool perimeter (4' for pools over 44' long).
- Using chalk or dot stickers begin marking points along the perimeter of the pool wall in a counterclockwise direction. The marks should be at **2' to 3'** intervals. Mark sharp radius at **1' to 2'** intervals. Straight lines can be marked at **3' to 4'** intervals. Mark all corner points, ladders, hand-rails, grab-rails, slide legs, rocks, spillways, spa walls, fill spouts, etc.
- Measure and record distance from **point A to point #1**, then **point A to #2**, and so on for all the **# points** around the pool. Then measure and record from **point B to each of the # points** around all of the pool. List all of the measurements in the correct blank on the next page.
- Measure the length and width of the pool at the waterline using 2 of your numbered points for each.
- Draw a freehand sketch of the pool indicating the inside dimensions. Include the **"A-B"** line location, deck area, planters and any obstructions within **3'** of the waterline. **Please indicate on the drawing which side A & B are on if you are standing at the shallow end.** A photo of the pool is suggested when rocks, waterfalls, raised walls, spas or any other obstructions. It is recommended to take pictures of the numbered points at obstructions.

	A	B
1		
2	Complete All!	Complete All!
3		
4		
5		
6		
7		
8		
9		
10		
11		

